

MULTIPURPOSE

LOW SHOES


S3 SRC

The +

- Footbridge supplying torsional rigidity.
- Padding for snug fit.
- Also available on request (Reference: 9FEHH) with an electrical hazards resistant outsole (ASTM F-2413-11 EH).



PURCHASE PACKAGING

REF.	EU	US	
9FREL36	36	4	10
9FREL37	37	4.5	10
9FREL38	38	5.5	10
9FREL39	39	6	10
9FREL40	40	7	10
9FREL41	41	8	10
9FREL42	42	8.5	10
9FREL43	43	9.5	10
9FREL44	44	10	10
9FREL45	45	11	10
9FREL46	46	11.5	10
9FREL47	47	12.5	10
9FREL48	48	13.5	10

DESCRIPTION

Upper in granulated leather, water repellent
 External sole in PU double density
 Antipenetration textile sole, nonmagnetic
 Composite toecap, nonmagnetic
 Breathable textile lining

SECTORS

Service

Second work

Infrastructure, building industry

Transport and logistics

APPLICATIONS EXAMPLES

- Luggage handler,
- Delivery driver, ...

See also

Variant



9FREH

TECHNICAL FEATURES

Closure	Lacing	Anti perforation sole	Textile
Toe cap	Composite	Reflective trim	At the back
Reinforced part of shoe	Footbridge supplying torsional rigidity	Padding	Padded bracelet and tongue
Examples of applications	Luggage handler, Delivery driver, ...	Color	Black
Upper	Full grain leather	Insole	Removable, textile and foam
Loops	Plastic hooks	Midsole	Injected polyurethane
Wearing sole	Polyurethane	Main assembly	Injected assembly
Lining	Breathable 3D mesh		

INSTRUCTIONS FOR USE AND STORAGE

Instructions for use :

- These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions :

- Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Cleaning instructions :

- Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

LEGISLATION

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **LEC F100361858**. Delivered by **INTERTEK (362)**.

EN ISO 20345:2011

S3 **SRC**

S3 : A 200 Joule impact and 15 000 Newton compression resistant toe-cap / Closed heel / Antistatic shoe $0,1M\Omega < A < 1000 M\Omega$ / Fuel and oil resistant contact outsole / Energy absorbing heel $E \geq 20$ Joules / Puncture resistant midsole : resistant to a 1 100 Newtons pressure / Water penetration and absorption resistant upper / Spiked outsole
SRC : Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

PPE CAT. II

Major risks

Retailer stamp