

KUBE

KAYAK S3 KU025T

CE UNI EN ISO 20345:2012 S3 SRC ESD CLASS 3

Low shoe, suede back leather WRU thickness 1,8-2,0 mm.
Highly perspiring and abrasion resistant fabric lining.
Shoe with refracting fabric insert.
Soft, lined and padded tongue.

COMPLETELY METAL FREE SHOE

TOECAP 200J polymeric composite non-thermic according to EN 12568

MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE KUBE bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE 5000, three-materials extracomfort: perspiring, removable, anatomic, absorbing, ESD and anti-bacterial

The shoe satisfies the requirement according to the norm IEC 61340-4-3:2001 for the electrical resistance **ESD class 3 (electric dissipative footwear)**


Size 36-47 Shoe weight Sz 42 gr. 550



MATERIALS



TECHNOLOGIES



SECTORS



SOLE



In order to avoid the high number of accidents caused by slipping danger, Giasco realized an **excellent anti-slipping product**.

This sole is called **Kube**, a young and sporty styled shoe equipped with a special gripping compound and specific cubic dowels with inverted profile in the outsole.

With thanks to these special characteristics Kube obtained the maximum certification against slipping: **jobs on inclined roofs** (UNI 11583:2015).

PLUS

ANTISLIPPING TEST RESULTS

SRC ANTI-SLIPPING SOLE		VERY GOOD
SRA ceramic + NaLS	HEEL >= 0,28	0,46
	FLAT >= 0,32	0,43
SRB steel + glycerol	HEEL >= 0,13	0,30
	FLAT >= 0,18	0,29

