

# SNAKE 02 FO

C71810

CE UNI EN ISO 20347:2012 O2 FO SRC ESD

Low shoe, MICROWASH thickness 1,8-2,0 mm.  
Perspiring and abrasion resistant fabric lining.

**COMPLETELY METAL FREE SHOE**

**SOLE CITY** bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

**INSOLE 5000, three-materials extracomfort:** perspiring, removable, anatomic, absorbing, ESD and anti-bacterial

**FO** sole resistance to hydrocarbons



The shoe satisfies the requirement according to the norm IEC 61340-4-3:2017 (IEC 61340-5-1:2016) for the electrical resistance **ESD**

**Size 36-47 Shoe weight Sz 42 gr. 440**

## CERTIFICATIONS



## TECHNOLOGIES AND MATERIALS



## SECTORS



## SOLE



City is a unique styled shoe, perfect for people who look for a safety shoe to use in a lot of different situations, free time included. Giasco developed for this product a special gel insert in the heel zone, called G-GEL, useful to reduce the impact stress et to release energy during walking. This sole has been studied with a special attention to the design of uppers and sole and to the technology of hidden outsole.


## PLUS



### MICROWASH

MICRO WASH is a Chrome free material finished with perspiring polyurethanes. Very light and perspiring, it is suitable for alimentary et hospital sectors. It is also studied for people wearing the shoes for a lot of hours on wet surfaces. It resists to acids, mostly oleic acid. It is washable with water and neutral soap at 40°.

## ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS		
	<b>SRC</b>	
	ANTI-SLIPPING SOLE	
<b>SRA</b> ceramic + NaLS	HEEL >= 0,28	0,52
	FLAT >= 0,32	0,52
<b>SRB</b> steel + glycerol	HEEL >= 0,13	0,18
	FLAT >= 0,18	0,20