

TECHNICAL DATASHEET MO23106

Ref. MO23106

Non Reusable



FFP1 NR D

The +

Electrostatic filter media
Elastic band without latex
Adjustable alu nose clip and comfortale
nasal cushions with polyethylene foam

Exhalation valve: reduction of breathing resistance and avoid fog inside the mask

PURCHASE PACKAGING

Référence Taille Sachet Carton 23106 12

DESCRIPTION

FFP1 disposable half mask in non-woven polypropylene with exhalation valve, latex free synthetic rubber

SECTORS

Farming, silviculture and fishing

Mining

Light Industries

Maintenance

Infrastructure, building industry

Construction - finishing work

DIY

APPLICATIONS

For occasional use in a very dusty environment. Protections against non-toxic solid and liquid aerosols, such as calcium carbonate, kaolin, cement, cellulose, sulfur, cotton, flour, coal, ferrous metals, vegetable oils and tender woods.

Textile industry, craft industry, metallurgical industry, mining industry, underground civil engineering, woodwork (strong woods excepted).

TECHNICAL FEATURES

Features FFP1 Weight 12g

Shape Shell mask with valve

Specifications FFP1 NR D

Harness features Synthetic elastic rubber (latex free)
Main risk Respiratory protection from aerosols

and non toxic dust

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate 697918 Delivered by BSI Assurance UK Ltd (0086) Kitemark Court Davy Avenue Knowlhill Milton Keynes MK5 8PP United Kingdom



EN149:2001 / A1:2006

Particle filtering half masks

FFP1

RETAILER STAMP

MAJ 04/03/2021