

## **BLS 700 SERIES** *DISPOSABLE FLAT RESPIRATORS*

The disposable respirators BLS 700 series offer effective respiratory protection in environments where the user is exposed to airborne solid and / or liquid particles (dust, fumes, mists).



### *Features /*



#### **FLAT THREE-PANEL DESIGN AND SINGLE PACK**

The mask is suitable for different types of faces with different sizes and shapes, it is comfortable to wear and easy to store when not in use. The single hygienic packaging also protects the respirator from any contamination before use, allowing its conservation in a practical way and the distribution in the work environment.

#### **INTERNAL NOSE CLIP**

The nose clip, placed internally between the layers of the filtering material, adapts optimally to the nose and eye profile of any type of face, ensures good visibility and optimized compatibility with glasses.

#### **AVAILABLE WITH EXHALATION VALVE**

It allows the exhaled air to dissipate more easily and ensures a high comfort to the user, making the respirator suitable for humid warm working environments.

# BLS 700 SERIES

## DISPOSABLE FLAT RESPIRATORS

### MATERIALS

HARNESS	Stapled thermoplastic elastomer (TPE)
NOSE CLIP	Reinforced Polypropylene (PP)
VALVE	Polypropylene (PP); rubber
FILTERING MEDIUM	Polypropylene (PP)

All components in direct contact with user's face are LATEX FREE

### TECHNICAL DATA

CODE	MODEL	CLASS of PROTECTION	VALVE
8006261	BLS 728	FFP2 NR D	—
8006225	BLS 729	FFP2 NR D	V
8006244	BLS 760	FFP3 R D	V

(NR) Not Reusable, 8 hours max (R) Reusable

(TLV) Threshold Limit Value (NPF) Nominal Protection Factor

(D) The product passed Dolomite test, simulates a heightened level of solid particles

### CERTIFICATION

BLS respirators are:

- certified according to the European Regulation 425/2016 (Personal protective equipments)
- certified as PPE of III category, in presumption of conformity to harmonized standard EN 149:2001+A1 2009
- certified and controlled according to Annex D by Italcert S.r.l. (Notified Body n°0426)
- CE marked

BLS management system is ISO 9001 certified

### IMPORTANT

BLS declines any responsibility, direct or indirect, from any misuse of both devices and instructions.

User is responsible for the determination of product compliance with the intended use.

### STORAGE

SHELF-LIFE	10 years
TEMPERATURE	+ 5° C / + 40° C
RELATIVE HUMIDITY	< 60 %

# BLS 700 SERIES

## DISPOSABLE FLAT RESPIRATORS

### TRANSPORT

MODEL	CODE	WEIGHT (g)	Q.TY / BOX	Q.TY / CARTON	CARTON WEIGHT (Kg)	Q.TY / PALLET
BLS 728	8006261	11	20	320	6,6	9600
BLS 729	8006225	15	10	160	5,1	4800
BLS 760	8006244	21	10	160	5,5	4800

### AVAILABLE MODELS



BLS 728

BLS 729 - BLS 760

### SELECTION GUIDE

#### FLAT \_ ALL MODELS

- Prevents the contamination of the inner mask before and after use
- It can be sold in vending machines
- Ideal for intermittent use, no damage if kept in the pockets

#### NO VALVE \_ BLS 728

- Also protects the environment from the user
- Ideal in the medical or food industry and all working environments where contamination from the user must be avoided

#### WITH VALVE \_ BLS 729 / BLS 760

- Reduces respiratory resistance and stagnation of heat providing comfortable protection, even in hot and humid environments