

Ref. **9BONO10**

Indoor and dry environments

Low

Sandals



S1

SR

FO



The +

*Open shoe to be protected without suffering from heat.

*Defined heel for better safety especially on ladders.

PURCHASE PACKAGING

Ref.	Size	Carton
9BONO10035	35	10
9BONO10036	36	10
9BONO10037	37	10
9BONO10038	38	10
9BONO10039	39	10
9BONO10040	40	10
9BONO10041	41	10
9BONO10042	42	10
9BONO10043	43	10
9BONO10044	44	10
9BONO10045	45	10
9BONO10046	46	10
9BONO10047	47	10
9BONO10048	48	10

Some sizes may only be available in certain countries

DESCRIPTION

BONO shoe is a shoe with a nubuck leather upper, reflective trim on both sides and moisture wicking non-woven lining. This open shoe permits to be protected without suffering from heat. This model is equipped of a steel toe cap a for a better protection against perforation and falling of heavy objects. It has a fuel and oil resistant contact outsole on ceramic or steel floor.

SECTORS

Light Industries

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

TECHNICAL FEATURES

Color	Black	Closing	Scratch closure
Weight	545 g	Lining	Breathable 3D mesh
Upper	Nubuck leather		
Toecap	Steel		
Midsole	PU		
Outsole	PU		
Insole	Removable, perforated EVA		
Main assembly	Injected		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/08/23/1304 EXT 01/10/23

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2022

Safety shoes

EN ISO 20345:2022
S1

S1 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe $0,1M \Omega < A < 1000 M \Omega$ + Fuel and oil resistant contact outsole + Energy absorbing heel $E \geq 20$ Joules

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance