

Specialties

High

High shoes



The +

- *Good resistance to hydrolysis.
- *Value for money.

PURCHASE PACKAGING

Référence	Taille	Carton
9LAH052038	38	10
9LAH052039	39	10
9LAH052040	40	10
9LAH052041	41	10
9LAH052042	42	10
9LAH052043	43	10
9LAH052044	44	10
9LAH052045	45	10
9LAH052046	46	10
9LAH052047	47	10

DESCRIPTION

The LAZURITE S3 model is a high safety shoe. Its upper is made up of black and blue action leather. Its toe cap and plate are in steel. This model has a polyester lining and an EVA insole. The collar and the tongue are padded for a snug fit. This shoe has 5 metal eyelets. Its outsole in PU/rubber is anti-slip on steel floors and hydrocarbons resistant.

SECTORS

Infrastructure, building industry

Construction - finishing work

Transport (excluding manufacturing) and logistics

Services and distribution

TECHNICAL FEATURES

Color	Black	Closing	Lacing closure
Color 2	Blue	Lining	Breathable 3D mesh
Upper	Action leather		
Toecap	Steel		
Puncture resistant sole	Stainless steel		
Midsole	PU		
Outsole	Rubber nitrile		
Insole	Textile and foam, removable		
Main assembly	Injected		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)



EN ISO 20345:2011

S3

SRC

EPI CAT. I

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe $0,1M\Omega < A < 1000 M\Omega$ + Fuel and oil resistant contact outsole + Energy absorbing heel $E \geq 20$ Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

RETAILER STAMP