

Ref. **9MAN150**

Indoor

Low

Low shoes



### The +

- \*Value for money.
- \*Breathable upper and lining.
- \*Wide range of sizes.
- \*Insole with silicone insert: comfort.

### PURCHASE PACKAGING

| Référence  | Taille | Carton |
|------------|--------|--------|
| 9MAN150036 | 36     | 6      |
| 9MAN150037 | 37     | 6      |
| 9MAN150038 | 38     | 6      |
| 9MAN150039 | 39     | 6      |
| 9MAN150040 | 40     | 6      |
| 9MAN150041 | 41     | 6      |
| 9MAN150042 | 42     | 6      |
| 9MAN150043 | 43     | 6      |
| 9MAN150044 | 44     | 6      |
| 9MAN150045 | 45     | 6      |
| 9MAN150046 | 46     | 6      |
| 9MAN150047 | 47     | 6      |
| 9MAN150048 | 48     | 6      |

### DESCRIPTION

MANGANITE is a low shoe in micro-perforated suede leather with an moisture wicking non-woven lining. This model has a steel toecap and an anti-perforation sole in stainless steel for a better protection. Its outsole is resistant to hydrocarbons and slipping on ceramic and metal floors. The insole with silicone insert provides additional comfort.

### SECTORS

Light Industries

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

## TECHNICAL FEATURES

|                                |                           |               |                                     |
|--------------------------------|---------------------------|---------------|-------------------------------------|
| <b>Color</b>                   | Anthracite                | <b>Lining</b> | Moisture wicking non-woven membrane |
| <b>Upper</b>                   | Suede leather             |               |                                     |
| <b>Toecap</b>                  | Steel                     |               |                                     |
| <b>Puncture resistant sole</b> | Stainless steel           |               |                                     |
| <b>Midsole</b>                 | PU                        |               |                                     |
| <b>Outsole</b>                 | PU                        |               |                                     |
| <b>Insole</b>                  | Removable, perforated EVA |               |                                     |
| <b>Main assembly</b>           | Injected                  |               |                                     |
| <b>Closing</b>                 | Lacing closure            |               |                                     |

## INSTRUCTION FOR USE AND STORAGE

**Instructions for use**

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

**Storage instructions**

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

**Washing instructions**

Regularly clean the shoes by using brushes, cleaning clothes.

## STANDARD(S)



EN ISO 20345:2011

S1P

SRC

## EPI CAT. I

Safety shoes

**S1P** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe  $0,1M\Omega < A < 1000 M\Omega$  + Fuel and oil resistant contact outsole + Energy absorbing heel  $E \geq 20$  Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

RETAILER STAMP