

Indoor

Low

Low shoes



### The +

- \* Sporty style
- \* Breathability
- \* Front reinforcement
- \* PU2D injected sole

### PURCHASE PACKAGING

| Référence  | Taille | Carton |
|------------|--------|--------|
| 9MIL530038 | 38     | 10     |
| 9MIL530039 | 39     | 10     |
| 9MIL530040 | 40     | 10     |
| 9MIL530041 | 41     | 10     |
| 9MIL530042 | 42     | 10     |
| 9MIL530043 | 43     | 10     |
| 9MIL530044 | 44     | 10     |
| 9MIL530045 | 45     | 10     |
| 9MIL530046 | 46     | 10     |
| 9MIL530047 | 47     | 10     |

### DESCRIPTION

MILERITE S1P is a low safety shoe inspired by sport design with mesh upper and a lining which offer high breathability and comfort. The front reinforcement made of embossed leather is suitable for users working squatting or kneeling. It ensures longer lifetime. Its double density PU outsole resists to fuel and oil contact. It is slip-resistant on ceramic or steel floor and offers excellent shock absorption. Its removable insole, made of textile and EVA with wide perforations, offers good evacuation of perspiration. MILERITE features a toe-cap and an anti-penetration plate made of steel for optimal protection. It is ideal for work dry environments.

### SECTORS

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

### APPLICATIONS

Painter,  
Electrician,  
Storekeeper, ...

## TECHNICAL FEATURES

|                                |                           |                |                    |
|--------------------------------|---------------------------|----------------|--------------------|
| <b>Color</b>                   | Grey                      | <b>Closing</b> | Lacing closure     |
| <b>Color 2</b>                 | Red                       | <b>Lining</b>  | Breathable 3D mesh |
| <b>Upper</b>                   | Mesh                      |                |                    |
| <b>Toecap</b>                  | Steel                     |                |                    |
| <b>Puncture resistant sole</b> | Stainless steel           |                |                    |
| <b>Midsole</b>                 | PU                        |                |                    |
| <b>Outsole</b>                 | PU                        |                |                    |
| <b>Insole</b>                  | Removable, perforated EVA |                |                    |
| <b>Main assembly</b>           | Injected                  |                |                    |

## INSTRUCTION FOR USE AND STORAGE

**Instructions for use**

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

**Storage instructions**

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

**Washing instructions**

Regularly clean the shoes by using brushes, cleaning clothes.

## STANDARD(S)



EN ISO 20345:2011

S1P

SRC

## EPI CAT. II

Safety shoes

**S1P** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe  $0,1M\Omega < A < 1000 M\Omega$  + Fuel and oil resistant contact outsole + Energy absorbing heel  $E \geq 20$  Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

RETAILER STAMP