

Ref. **9OKEC**

Specialties

Low



### The +

- \*Easy-on and easy-off.
- \*Lightweight for use all day long.
- \*Semi-closed heel for extra stability.
- \*Antistatic outsole (A).
- \*Energy absorbing heel (E).

### PURCHASE PACKAGING

Référence	Taille	Carton
9OKEC35	35	10
9OKEC36	36	10
9OKEC37	37	10
9OKEC38	38	10
9OKEC39	39	10
9OKEC40	40	10
9OKEC41	41	10
9OKEC42	42	10
9OKEC43	43	10
9OKEC44	44	10
9OKEC45	45	10
9OKEC46	46	10
9OKEC47	47	10

### DESCRIPTION

Composite toecap  
External sole in double density PU/PU  
Upper: breathable Microfiber in PU  
Breathable mesh lining

### SECTORS

Food-processing industry

Regional/public authorities

Construction - finishing work

Transport (excluding manufacturing) and logistics

## TECHNICAL FEATURES

<b>Color</b>	White	<b>Lining</b>	Breathable 3D mesh
<b>Color 2</b>	Grey		
<b>Upper</b>	Microfiber		
<b>Toecap</b>	Composite		
<b>Midsole</b>	PU		
<b>Outsole</b>	PU		
<b>Insole</b>	Removable, textile and foam		
<b>Main assembly</b>	Injected		
<b>Closing</b>	Back scratch strap		

## INSTRUCTION FOR USE AND STORAGE

**Instructions for use**

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

**Storage instructions**

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

**Washing instructions**

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **LEC FI00342733**

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom

**EPI CAT. I****EN ISO 20345:2011****SB****SRC****ESD**

Safety shoes

**SB** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

Electrostatic discharge shoe (CEI EN 61340-4-3 standard)

RETAILER STAMP