

Specialties

Low

Low shoes



HRO



The +

- * Breathable upper and lining.
- * Heel scuff cap.
- * Padding for snug fit.
- * Rounded heel for more comfortable driving.

PURCHASE PACKAGING

Référence	Taille	Carton
9RUBL36	36	10
9RUBL37	37	10
9RUBL38	38	10
9RUBL39	39	10
9RUBL40	40	10
9RUBL41	41	10
9RUBL42	42	10

DESCRIPTION

Composite toecap
Antipenetration textile Wellmax® sole
External sole in Rubber
Plastic eyelets
Upper in Nubuck

SECTORS

Food-processing industry

Regional/public authorities

Construction - finishing work

Transport (excluding manufacturing) and logistics

TECHNICAL FEATURES

Color	Black	Reinforcement material	Anti-abrasion Stark®
Color 2	Grey	Reinforcement location	Heel
Upper	Polyamide mesh / Nubuck leather	Closing	Lacing closure
Toecap	Composite	Lining	Breathable 3D mesh
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	Rubber nitrile		
Insole	Attached, textile and foam		
Main assembly	Injected		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **LEC FI00332900**

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EN ISO 20345:2011

S3

SRA

HRO

EPI CAT. II

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe $0,1M\Omega < A < 1000 M\Omega$ + Fuel and oil resistant contact outsole + Energy absorbing heel $E \geq 20$ Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

Heat contact resistant outsole (60 seconds at 300°C)

RETAILER STAMP