coverguard

TECHNICAL DATASHEET **SILVER**

Ref. 9SIH150

Multipurpose

High









DESCRIPTION

SILVER is a waterproof shoe, in suede and nylon.

The breathability of the materials that make up this model make it a safety shoe with comfortable use and long-lasting performance.

Equipped with a steel toe cap and midsole, it also features a dual density PU outsole.

The shoe is designed to resist slipping on steel and ceramic floors

SECTORS

Light Industries

Construction - finishing work

Transport (excluding manufacturing) and logistics

Services and distribution





The +

- *Breathable and water repellent upper.
- *Reflective stripe with multiple faces.
- *Heel and toe scuff cap.

PURCHASE PACKAGING

Référence	Taille	Carton
9SIH150037	37	6
9SIH150038	38	6
9SIH150039	39	6
9SIH150040	40	6
9SIH150041	41	6
9SIH150042	42	6
9SIH150043	43	6
9SIH150044	44	6
9SIH150045	45	6
9SIH150046	46	6
9SIH150047	47	6

TECHNICAL FEATURES

Anthracite Moisture wicking non-woven membrane Color Lining

Toecap Steel

Stainless steel Puncture resistant sole

Midsole PU PU **Outsole**

Insole Textile and foam, removable

Main assembly Injected Closing Lacing closure

INSTRUCTION FOR USE AND STORAGE

Suede leather / Polyamide mesh

Instructions for use

Upper

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)

Safety shoes

EPI CAT. II

EN ISO 20345:2011 **S3**

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap

- + Closed heel + Antistatic shoe $0.1 \text{M}\Omega < A < 1000 \text{ M}\Omega$ + Fuel and oil resistant contact outsole
- + Energy absorbing heel E ≥ 20 Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

RETAILER STAMP

MAJ 23/02/2021