

Multipurpose

Low

Low shoes



The +

- *Breathable and water repellent upper.
- *Heel and toe scuff cap.
- *Reflective stripe with multiple faces.

PURCHASE PACKAGING

Référence	Taille	Carton
9SIL150037	37	6
9SIL150038	38	6
9SIL150039	39	6
9SIL150040	40	6
9SIL150041	41	6
9SIL150042	42	6
9SIL150043	43	6
9SIL150044	44	6
9SIL150045	45	6
9SIL150046	46	6
9SIL150047	47	6

DESCRIPTION

SILVER is a waterproof shoe, in suede and nylon. The breathability of the materials that make up this model make it a safety shoe with comfortable use and long-lasting performance. Equipped with a steel toe cap and midsole, it also features a dual density PU outsole. The shoe is designed to resist slipping on steel and ceramic floors.

SECTORS

Light Industries

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

TECHNICAL FEATURES

Color	Anthracite	Lining	Moisture wicking non-woven membrane
Upper	Suede leather / Polyamide mesh		
Toecap	Steel		
Puncture resistant sole	Stainless steel		
Midsole	PU		
Outsole	PU		
Insole	Textile and foam, removable		
Main assembly	Injected		
Closing	Lacing closure		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)



EN ISO 20345:2011

S3

SRC

EPI CAT. I

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe $0,1M\Omega < A < 1000 M\Omega$ + Fuel and oil resistant contact outsole + Energy absorbing heel $E \geq 20$ Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

RETAILER STAMP