

Ref. **9SPIL**

Multipurpose

Low

Low shoes



The +

- * Breathable upper and lining.
- * 3 metal ventilation eyelets on the inner side.
- * Padded collar and tongue for snug fit.

PURCHASE PACKAGING

Référence	Taille	Carton
9SPIL34	34	10
9SPIL35	35	10
9SPIL36	36	10
9SPIL37	37	10
9SPIL38	38	10
9SPIL39	39	10
9SPIL40	40	10
9SPIL41	41	10
9SPIL42	42	10
9SPIL43	43	10
9SPIL44	44	10
9SPIL45	45	10
9SPIL46	46	10
9SPIL47	47	10
9SPIL48	48	10
9SPIL49	49	10

DESCRIPTION

Steel toecap
 Antipenetration steel sole
 External sole in double density PU/PU
 Upper in Suede
 Breathable mesh lining
 Non woven lining
 Polyester belLow shoess padded
 Padded collar
 3 breathable holes

SECTORS

Infrastructure, building industry

Construction - finishing work

Transport (excluding manufacturing) and logistics

Services and distribution

APPLICATIONS

Luggage handler,
 Delivery driver, ...

TECHNICAL FEATURES

Color	Grey	Closing	Lacing closure
Color 2	Orange	Lining	Breathable 3D mesh
Upper	Suede leather / Mesh		
Toecap	Steel		
Puncture resistant sole	Stainless steel		
Midsole	PU		
Outsole	PU		
Insole	Removable, textile and foam		
Main assembly	Injected		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The tim influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **LEC FI00342259**

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EPI CAT. II

EN ISO 20345:2011

S1P

Safety shoes

S1P Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe $0,1M\Omega < A < 1000 M\Omega$ + Fuel and oil resistant contact outsole + Energy absorbing heel $E \geq 20$ Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

RETAILER STAMP