

Ref. **9SUN**

Indoor

Low

Low shoes



The +

- * Breathable upper and lining.
- * Wide range of sizes (2 to 13.5).

PURCHASE PACKAGING

Référence	Taille	Carton
9SUN34	34	10
9SUN35	35	10
9SUN36	36	10
9SUN37	37	10
9SUN38	38	10
9SUN39	39	10
9SUN40	40	10
9SUN41	41	10
9SUN42	42	10
9SUN43	43	10
9SUN44	44	10
9SUN45	45	10
9SUN46	46	10
9SUN47	47	10
9SUN48	48	10
9SUN49	49	10

DESCRIPTION

SUN is a low shoe in micro-perforated suede leather with an moisture wicking non-woven lining. This model has a steel toecap and an anti-perforation sole in stainless steel for a better protection. Its outsole is resistant to hydrocarbons and slipping on ceramic and metal floors.

SECTORS

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

APPLICATIONS

Painter,
Electrician,
Storekeeper, ...

TECHNICAL FEATURES

Color	Blue grey	Lining	Moisture wicking non-woven membrane
Upper	Suede leather		
Toecap	Steel		
Puncture resistant sole	Stainless steel		
Midsole	PU		
Outsole	PU		
Insole	Removable, textile and foam		
Main assembly	Injected		
Closing	Lacing closure		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The tim influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **LEC FI00342259**

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EPI CAT. II

EN ISO 20345:2011

S1P

Safety shoes

S1P Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe $0,1M\Omega < A < 1000 M\Omega$ + Fuel and oil resistant contact outsole + Energy absorbing heel $E \geq 20$ Joules + Puncture resistant midsole / Resistant to a 100 Newtons pressure

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

RETAILER STAMP