

Outdoor

Low

Low shoes



HRO



The +

- * Footbridge supplying torsional rigidity.
- * Padded collar and bellows tongue for snug fit.

PURCHASE PACKAGING

Référence	Taille	Carton
9TOPL38	38	10
9TOPL39	39	10
9TOPL40	40	10
9TOPL41	41	10
9TOPL42	42	10
9TOPL43	43	10
9TOPL44	44	10
9TOPL45	45	10
9TOPL46	46	10
9TOPL47	47	10

DESCRIPTION

Composite toecap
 Antipenetration textile sole
 External sole in double density PU/Rubber
 Upper in crazy horse leather
 Breathable mesh lining
 Reinforcement : front in PU and back in TPU

SECTORS

- Mining
- Extracting Oil and Gas
- Energy
- Infrastructure, building industry

APPLICATIONS

Builder,
 Slater,
 Ramp agent,
 Luggage handler,
 Site supervisor,
 Docker, ...

TECHNICAL FEATURES

Color	Brown	Closing	Lacing closure
Color 2	Orange	Lining	Breathable 3D mesh
Upper	Full grain leather		
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	Rubber nitrile		
Insole	Removable, textile and foam		
Main assembly	Injected		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **LEC FI00341289**

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EN ISO 20345:2011

S3

SRC

HRO

EPI CAT. II

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe $0,1M\Omega < A < 1000 M\Omega$ + Fuel and oil resistant contact outsole + Energy absorbing heel $E \geq 20$ Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

Heat contact resistant outsole (60 seconds at 300°C)

RETAILER STAMP