

TECHNICAL DATASHEET MO23205

Ref. MO23205

Non Reusable





FFP2 NR D



The +

Electrostatic filter media
Sliding elastic band: better adjustment
Latex free to prevent the risk of irritation
Exhalation valve: reduction of breathing
resistance and avoid fog inside the mask

PURCHASE PACKAGING

Référence Taille Sachet Carton 23205 12

SALES PACKAGING



Individual pack

DESCRIPTION

Foldable half-mask in nonwoven polypropylene with exhalation valve, latex free synthetic rubber, adjustable nose clip

SECTORS

Heavy & process industries

Chemical & pharmaceutical industries

Light Industries

Infrastructure, building industry

Construction - finishing work

DIY

APPLICATIONS

For occasional use in a very dusty environment. Protections against non-toxic solid and liquid aerosols, such as calcium carbonate, kaolin, cement, cellulose, sulfur, cotton, flour, coal, ferrous metals, vegetable oils and tender woods.

Textile industry, craft industry, metallurgical industry, mining industry, underground civil engineering, woodwork (strong woods excepted).

TECHNICAL FEATURES

Features FFP2

Other features Polypropylene Welded contour

Weight 17g

Shape Flat foldable half mask with valve

Specifications FFP2 NR D

Harness features Synthetic elastic rubber (latex free)

Main risk Respiratory protection from aerosols

and low toxic dust

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate 697918 Delivered by BSI Assurance UK Ltd (0086) Kitemark Court Davy Avenue Knowlhill Milton Keynes MK5 8PP United Kingdom



EN149:2001 / A1:2006

Particle filtering half masks

FFP2 NR D

RETAILER STAMP

MAJ 04/03/2021