

Non Reusable

FFP2 NR D organic vapours gas and acids



The +

- Electrostatic filter media which filters bad odours
- Exhalation valve: reduction of breathing resistance and avoid fog inside the mask
- Adjustable alu nose clip and comfortable nasal cushions with polyethylene foam
- Latex free elastic bands

PURCHASE PACKAGING

Référence	Taille	Sachet	Carton
23238			12

DESCRIPTION

FFP2 half-mask made of non-woven polypropylene with exhalation valve and active carbon, latex free synthetic rubber, aluminum adjustable nose clip, PU foam nose pad

SECTORS

- Heavy & process industries
- Chemical & pharmaceutical industries
- Light Industries
- Infrastructure, building industry
- Construction - finishing work
- DIY

APPLICATIONS

For occasional use in a very dusty environment. Protections against non-toxic solid and liquid aerosols, such as calcium carbonate, kaolin, cement, cellulose, sulfur, cotton, flour, coal, ferrous metals, vegetable oils and tender woods.
Textile industry, craft industry, metallurgical industry, mining industry, underground civil engineering, woodwork (strong woods excepted).

TECHNICAL FEATURES

Features	FFP2	Main risk	Respiratory protection from aerosols and low toxic dust, organic vapours, gas and acids
Weight	Polyester / polypropylène SMS		
Shape	17g		
Specifications	Half-mask with shell and carbon valve		
	FFP2 NR D organic vapours gas and acids		
Harness features	Synthetic elastic rubber (latex free)		

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **697918**

Delivered by BSI Assurance UK Ltd (0086) Kitemark Court Davy Avenue Knowlhill Milton Keynes MK5 8PP United Kingdom



EN149:2001 / A1:2006

FFP2 NR D

Particle filtering half masks

RETAILER STAMP

MAJ 04/03/2021