

TECHNICAL DATASHEET MO23316

Ref. MO23316

Non Reusable





FFP3 NR D





The +

Specific design of the exhalation valve: high reduction of the breathing resistance Preformed design: fits with glasses or goggles to avoid the risk of condensation The ergonomic form offers an optimal adjustment to the face without nose clip.

PURCHASE PACKAGING

Référence	Taille	Sachet	Carton
23316			12

DESCRIPTION

FFP3 disposable preformed half-mask made of nonwoven polypropylene, external layer in polyester with exhalation valve, PU foam total nose seal, latex free synthetic rubber

SECTORS

Mining

Heavy & process industries

Chemical & pharmaceutical industries

Light Industries

Regional/public authorities

Infrastructure, building industry

Construction - finishing work

APPLICATIONS

For occasional use in a very dusty environment. Protections against non-toxic solid and liquid aerosols, such as calcium carbonate, kaolin, cement, cellulose, sulfur, cotton, flour, coal, ferrous metals, vegetable oils and tender woods.

Textile industry, craft industry, metallurgical industry, mining industry, underground civil engineering, woodwork (strong woods excepted).

TECHNICAL FEATURES

Color White

Features Polyester / polypropylene SMS

Weight 17g

Shape Preformed shell mask with valve

Specifications FFP3 NR D

Harness features Synthetic elastic rubber (latex free)
Main risk Respiratory protection from toxic

aerosols and dusts

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **697918**Delivered by BSI Assurance UK Ltd (0086) Kitemark Court Davy Avenue Knowlhill Milton Keynes MK5 8PP United Kingdom



EN149:2001 / A1:2006

Particle filtering half masks

FFP3 NR D

RETAILER STAMP

MAJ 04/03/2021