

VERDI S3

AC880BP

CE UNI EN ISO 20345:2012 S3 SRC

High shoe, water-resistant WRU leather thickness 1,8-2,0 mm.

Perspiring and abrasion resistant fabric lining.

Shoe with refracting fabric insert.

Lined and padded tongue.

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE antiperforation steel according to EN 12568

SOLE ACTION bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE 1000, in high density and open cells latex foam.

Absorbing, antistatic and perspiring

Size 36-49 Shoe weight Sz 42 gr. 550



CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS



FARMING AND MINING



COMPONENTS AND AUTOMOTIVE



WOOD

METAL CARPENTRY



BUILDING AND HEAVY INDUSTRY



LOGISTICS AND LIGHT INDUSTRY

SOLE



Action is a shoe studied for external jobs, with soft lines making it very light and comfortable.

PLUS

ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS			
SRC			
ANTI-SLIPPING SOLE			
SRA ceramic + NaLS	HEEL >= 0,28	0,39	
	FLAT >= 0,32	0,36	
SRB steel + glycerol	HEEL >= 0,13	0,26	
	FLAT >= 0,18	0,22	