

3M™ Safety Glasses 2820 Series

Technical datasheet



Product description

The 3M™ 2820 series offers maximum protection and a stylish modern design. Products feature a rimless wrap-around lens and temple arms with a pliable 'soft-touch' finish. The range includes clear, grey and amber lens options.

Product range

| Product ID | Description | Lens colour | Frame colour |
|------------|--|-------------|--------------|
| 2820 | 3M™ 2820 Safety Glasses with clear PC lens | Clear PC | Grey |
| 2821 | 3M™ 2821 Safety Glasses with grey PC lens | Grey PC | Grey |
| 2822 | 3M™ 2822 Safety Glasses with amber PC lens | Amber PC | Grey |

Typical applications

These products can be used in a wide range of applications including:

- ▶ Construction
- ▶ Engineering
- ▶ General assembly
- ▶ Inspection work
- ▶ Light duty maintenance and repair

Intended use

These products are intended for protection against high speed particles at low energy (F) at extreme temperature conditions, -5°C and +55°C, (T) in accordance with EN 166:2001.

These products also help protect against UV radiation in accordance with EN 170:2002 (clear and amber lenses), and sun glare in accordance with EN 172:1994 (grey).

A number of lens options are available for a variety of different applications:

- ▶ Clear – Good colour recognition and excellent UV protection
- ▶ Grey – Good for protection from sun glare.
- ▶ Amber – Enhanced contrast in low light condition e.g. surface inspection

Key features

- ▶ Design provides excellent coverage and good field of vision
- ▶ Optical Class 1 to allow prolonged comfortable wear
- ▶ Inclinable lens for easy adjustment and maximum comfort
- ▶ Offers excellent protection against UV radiation
- ▶ Simple, stylish design
- ▶ Lens coatings provide scratch resistance and anti-fogging

Use limitation

- ▶ Never modify or alter this product
- ▶ Do not use this product against hazards other than those specified in this document
- ▶ In accordance with EN 166:2001 safety spectacles cannot be tested and approved for use against liquid droplets. Where liquid protection is specified a suitable product should be considered, for example safety goggles

Standards and approval

These products are type examined by BSI Group, Notified Body number 2797.

These products are CE marked to the requirements of European Regulation (EU) 2016/425.

The applicable legislation can be determined by reviewing the Certificate and Declaration of Conformity at www.3M.com/Eye/certs

Materials listing

| Description | Material |
|-------------|-----------------|
| Lens | Polycarbonate |
| Temple arms | Polycarbonate |
| Temple tips | PVC |
| Ratchet | Nylon |
| Screws | Stainless steel |

Marking

The products have demonstrated compliance with the requirements of EN 166:2001 and associated standards and bear the following marks:

| Product ref | Lens marking | Frame marking |
|-------------|----------------|-----------------|
| 2820 | 2C-1.2 3M 1 FT | 3M EN 166 FT CE |
| 2821 | 5-2.5 3M 1 FT | 3M EN 166 FT CE |
| 2822 | 2-1.2 3M 1 FT | 3M EN 166 FT CE |

Explanation of marking

| Marking | Description |
|------------------------------------|--|
| 2-1.2, and 2C-1.2 (EN 170:2002) | UV protection. This product conforms to the requirements of the standard, providing UV protection for the complete specified range (210nm – 365nm). Products marked C provide good colour recognition. |
| 5-2.5 (EN 172:1994 as amended) | Sun-glare protection conforming to the requirements of the standard, providing UV protection for the complete specified range (280nm – 350nm). |
| 1 | Optical class |
| F | Impact protection against high speed particle at low energy (45m/s) |
| T | Tested for impact protection at extreme temperature conditions -5°C and +55°C |

IMPORTANT NOTICE

The use of the 3M product described within this document assumes that the user has previous experience of this type of product and that it will be used by a competent professional. Before any use of this product it is recommended to complete some trials to validate the performance of the product within its expected application.

All information and specification details contained within this document are inherent to this specific 3M product and would not be applied to other products or environment. Any action or usage of this product made in violation of this document is at the risk of the user.

Compliance to the information and specification relative to the 3M product contained within this document does not exempt the user from compliance with additional guidelines (safety rules, procedures). Compliance to operational requirements especially in respect to the environment and usage of tools with this product must be observed. The 3M group (which cannot verify or control those elements) would not be held responsible for the consequences of any violation of these rules which remain external to its decision and control.

Warranty conditions for 3M products are determined with the sales contract documents and with the mandatory and applicable clause, excluding any other warranty or compensation.

For more information on 3M products and services please contact 3M.

Personal Safety Division

3M United Kingdom PLC
3M Centre, Cain Road
Bracknell, Berkshire RG12 8HT
Tel.: 0870 60 800 60
www.3M.eu/Safety

3M Ireland Limited
The Iveagh Building
The Park, Carrickmines
Dublin 18
t: 1 800 320 500

Please recycle. Printed in the UK. © 3M 2020. 3M is a trademark of 3M Company. All rights reserved. OMG69675

