

Ref. 6PHP160

### Non Vented Helmet General Use



### The +

#### PERFORMANCE

- High resistance level (lateral deformation (LD), molten metal splashes (MM), low temperature - 30°C)
- ABS Shell
- CLASS 0: electrical insulation for use on low voltage installations up to 1000V a.c and 1500V d.c

#### COMFORT

- Integrated safety glasses
- Good fitting and lightweight feeling (head balance)
- Easy adjustment by ratchet
- Wide field of vision thanks to the short peak
- 3D textile sweatband

#### LIGHTWEIGHT

- 450g

Compatible with badge holder (6POBA) and earmuffs (6MX3000NSI)

#### DESCRIPTION

PHOENIX PRO safety helmet. ABS shell, 6 points suspension harness in polyethylene with 6 textile webbing, size adjustment by ratchet from 52 to 63cm, short peak, integrated safety glasses with anti-scratch K standard and anti-fog N standard, side euro slot adapters, 3D textile sweatband, 4 points chinstrap as a standard

#### SECTORS

- Heavy & process industries
- Mechanicals constructions
- Light Industries
- Regional/public authorities
- Infrastructure, building industry

#### APPLICATIONS

Construction site, building and public works, industry...

#### PURCHASE PACKAGING

Ref.	Size	Inner	Carton
6PHP160NSI	-		16

#### SALES PACKAGING



Individual pack

See also

## TECHNICAL FEATURES

Shell material	ABS
Color	HV Yellow
Color 2	Black
Weight	450g
Service life	Expiry date indicated under the peak Shelf life: 2 years in standard conditions
Harness features	6 points harness made of polyethelene 6 textile webbings
Value electric isolation	1000V a.c / 1500V d.c
Adjustment	Adjustment by ratchet from 52 to 63 cm
Main risk	Prevention from falling objects and head injuries or head trauma
Lens colour	Clear

Features	ABS Shell LDPE 6 points harness Size adjustment from 52 to 63 cm Class 0: electrical insulation up to 1000V a.c and 1500V d.c
----------	--

## STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate DPI/0497/2313

Delivered by CSI (0497) Cascina Traversagna- 21 20030 Senago (MI) Italy



EPI CAT. III

EN166:2001

Specifications (optical quality, resistance to usual risks, mechanical risks, resistance to impacts)

EN397:2012 + A1:2012

Industrial safety helmets

EN50365:2002

Electrically insulating helmets for use on low voltage installations (used for working on or near live parts of installations not exceeding 1,000 V AC or 1,500 V DC)

COVERPERF - Skincare



Dermatological safety approved after direct contact with the skin for 48 hours. No irritation was observed at the end of the test.

RETAILER STAMP

MAJ 26/04/2022