

Specialties

High

High shoes



HRO



The +

- * Footbridge supplying torsional rigidity.
- * Padded collar and bellows tongue for snug fit.
- * Electrical hazards resistant outsole (ASTM F-2413-17 EH).

PURCHASE PACKAGING

Référence	Taille	Carton
9TEEH37		10
9TEEH38	38	10
9TEEH39	39	10
9TEEH40	40	10
9TEEH41	41	10
9TEEH42	42	10
9TEEH43	43	10
9TEEH44	44	10
9TEEH45	45	10
9TEEH46	46	10
9TEEH47	47	10
9TEEH48		10

DESCRIPTION

The TOPAZ is a high safety shoe with a full grain leather upper and breathable 3D mesh lining. It has front and back reinforcements in order to ensure a better protection and a longer lifetime. It has an electrical hazards resistant outsole (ASTM F-2413-17 EH).

This metalfree safety shoe has a composite toecap and an anti-perforation textile sole which guarantees lightness.

SECTORS

- Mining
- Extracting Oil and Gas
- Energy
- Infrastructure, building industry
- Construction - finishing work

APPLICATIONS

Builder,
Slater,
Ramp agent,
Luggage handler,
Site supervisor,
Dockers, ...

TECHNICAL FEATURES

Color	Brown	Closing	Lacing closure
Color 2	Black	Lining	Breathable 3D mesh
Upper	Full grain leather		
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	Rubber nitrile		
Insole	Removable, textile and foam		
Main assembly	Injected		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The tim influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **LEC FI00341289**

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EPI CAT. II

EN ISO 20345:2011

S3

SRC

HRO

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe $0,1M\Omega < A < 1000 M\Omega$ + Fuel and oil resistant contact outsole + Energy absorbing heel $E \geq 20$ Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

Heat contact resistant outsole (60 seconds at 300°C)

RETAILER STAMP