

Ref. **9BLAC10**

Outdoor

High

High shoes



### The +

- \* PU/PU "soft" outsole: cushioning
- \* Defined heel: stability on ladder.
- \* Large side zip: easy to put on.
- \* Foam insole with cushioning : comfort

### PURCHASE PACKAGING

Ref.	Size	Carton
9BLAC10036	36	4
9BLAC10037	37	4
9BLAC10038	38	4
9BLAC10039	39	4
9BLAC10040	40	4
9BLAC10041	41	4
9BLAC10042	42	4
9BLAC10043	43	4
9BLAC10044	44	4
9BLAC10045	45	4
9BLAC10046	46	4
9BLAC10047	47	4
9BLAC10048	48	4
9BLAC10049	49	4

*Some sizes may only be available in certain countries*

### DESCRIPTION

BLACK STAR is a safety ranger, with a grained leather and Oxford fabric upper.

Its outsole is made of low density PU/PU, which makes the model comfortable.

BLACK STAR is equipped with a composite toe cap and a textile puncture resistant sole, for lightness and flexibility.

A large side zipper makes it easy to put on and take off.

### SECTORS

Extracting Oil and Gas

Manufacture of electrical and electronic equipment and machines

Regional/public authorities

Infrastructure, building industry

### APPLICATIONS

Builder,  
Slater,  
Ramp agent,  
Luggage handler,  
Site supervisor,  
Docker, ...

**TECHNICAL FEATURES**

Color	Black	Closing	Lacing closure
Upper	Oxford / Grained leather	Lining	Breathable 3D mesh
Toecap	Composite	Weight	695 g
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		
Insole	Removable, textile and foam		
Main assembly	Injected		

**INSTRUCTION FOR USE AND STORAGE**

**Instructions for use**

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

**Storage instructions**

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

**Washing instructions**

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

**STANDARD(S)**

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/12/21/2226

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S3

SRC

COVERPERF - Damping



Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

Shoes tested in a certified laboratory (CTC) offering excellent damping. Over 25% of the impact force is absorbed by the sole.

