

Ref. **9SAP120**

Multipurpose

Low

Low shoes



### The +

- \*Lightness.
- \* Flexibility.
- \* Comfort of use (insole foam HI-POLY + midsole EVA).
- \* Dynamic profile and degraded two-tone outsole.

### PURCHASE PACKAGING

Ref.	Size	Carton
9SAP120038	38	6
9SAP120039	39	6
9SAP120040	40	6
9SAP120041	41	6
9SAP120042	42	6
9SAP120043	43	6
9SAP120044	44	6
9SAP120045	45	6
9SAP120046	46	6
9SAP120047	47	6

*Some sizes may only be available in certain countries*

### DESCRIPTION

Inspired by the design of running sneakers, the SAPHIR model seduces with its sleek look.

Metal-free, SAPHIR has been designed to offer the wearer lightness, flexibility and breathability.

The emphasis is on comfort: composite toe cap, textile anti-perforation midsole and Hi-Poly foam sockliner with cushions.

The nitrile rubber outsole, non-slip on metal and steel floors, is also resistant to hydrocarbons and heat.

### SECTORS

Light Industries

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

## TECHNICAL FEATURES

Color	Black	Insole	HI-POLY foam
Color 2	Blue	Reinforcement material	TPU
Weight	497 g	Reinforcement location	Front
Upper	Polyester mesh	Closing	Lacing closure
Toecap	Composite	Lining	Breathable 3D mesh
Puncture resistant sole	Textile		
Midsole	EVA		
Outsole	Rubber nitrile		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate ITASLNB20013172

Delivered by INTERTEK Italia S.p.A. (2575) Via Guido Miglioli 2/A 20063 Cernusco sul Naviglio - Milano (MI) Italy



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

**S3** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

HRO

Heat contact resistant outsole (60 seconds at 300°C)

RETAILER STAMP

MAJ 17/02/2023