



NEXUS

259P-001 S3 M HI HRO SRC

Standard EN ISO 20345:2011

Sizes 38-48



Three-dimensional Spyder-Net lining with moisture absorption and release properties. Its special three-dimensional and non-deformable textile structure ensures lasting comfort, breathability and elasticity.

Extra comfortable collar.

Reflective material.

Two-component HYBRID PU-RUBBER HRO sole, developed to offer maximum performance in terms of safety and comfort. Slip-resistance sole tested to the SATRA laboratories on metal grating and wooden scaffold boards.



HYBRID PU-RUBBER

- Rubber Outsole HRO
- Fuel oil resistance sole (FO)
- Self-cleaning cleated sole to ensure maximum adherence to the ground
- Excellent abrasion resistance



Quick release lacing System.

TPU metatarsal protection certified according to the European standard ensures the foot from impacts.

Full grain Idrotech leather with high water resistance properties.

COMPO200 polymeric toe cap anti-puncture Txzero textile insert for extreme lightness, protection and flexibility.



	SRC Slip resistance
	A Antistatic
	P Perforation resistance
	Resistant to an impact of 200 Joules and compression of 15Kn
	E Energy absorption at the heel part
	FO Fuel oil resistance sole
	WRU Water penetration resistant upper
	HI Heat insulation of the sole
	HRO Heat resistant outsole
	M Metatarsal protection

Esolight 1.0 polyurethane midsole with reinforced Over cap. The low-density micro-cell polyurethane increase energy absorption ensuring comfort and lightness.

H-01

- Breathable and antistatic
- Shock absorption cell
- Anatomic insole for better walking comfort