

Ref. **9ACO010**

Multipurpose

Low

Low shoes



The +

Lightweight and flexible, suitable for daily use
Optimal compromise between durability and cost
Basket look

PURCHASE PACKAGING



DESCRIPTION

ACCESS ONE (S1P FO SR SC ESD) is a low safety shoe, versatile and functional, designed for daily use.

Its upper made of suede textile and mesh, combined with a breathable lining, provides good comfort throughout the day. The PU/PU Outsole ensures good grip and resistance to oils and hydrocarbons, while guaranteeing effective cushioning.

Equipped with a steel toe cap and a steel anti-penetration sole, it is ideal for dry environments.

Ref.	Size	Carton
9ACO010035	35	8
9ACO010036	36	8
9ACO010037	37	8
9ACO010038	38	8
9ACO010039	39	8
9ACO010040	40	8
9ACO010041	41	8
9ACO010042	42	8
9ACO010043	43	8
9ACO010044	44	8
9ACO010045	45	8
9ACO010046	46	8
9ACO010047	47	8
9ACO010048	48	8
9ACO010049	49	8
9ACO010050	50	8

Some sizes may only be available in certain countries

SECTORS

Light Industries

Manufacture of electrical and electronic equipment and machines

Regional/public authorities

Maintenance

Construction - finishing work

DIY

TECHNICAL FEATURES

Color	Black	Insole	EVA
Color 2	Grey	Main assembly	Injected
Weight	600 g	Front bumper	
Upper	Mesh / Nubuck leather	Reinforcement material	Microfiber
Toecap	Steel	Reinforcement location	Front
Puncture resistant sole	Steel	Closing	Lacing closure
Midsole	PU	Lining	Breathable 3D mesh
Outsole	PU		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can only be compliant with their protective Features if they fit perfectly and are well maintained. Before any use, perform a visual inspection to ensure they are in perfect condition and proceed with a fitting. It is advisable to choose the model that best meets the specific requirements of your workplace.

Storage instructions

Store the shoes in a dry, clean, and well-ventilated area. A storage duration exceeding 5 years is not recommended.

Washing instructions

Clean the shoes regularly using brushes, cloths, etc.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0598/PPE/26/0641 Issue 1

Delivered by SGS Fimko Oy (0598) Takomotie 8 00380 HELSINKI Finland



EPI CAT. II

ESD

Electrostatic discharge shoe (EN 61340-5-1 standard)

EN ISO 20345:2022

Safety shoes

+ A1:2024
S1P

S1P Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe $0,1M \Omega < A < 1000 M \Omega$ + Fuel and oil resistant contact outsole + Energy absorbing heel $E \geq 20$ Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure

SR

Resistance to slippage (ceramic floor + oil)

SC

Abrasion resistance of the toe-caps

FO

Hydrocarbons resistance