

SAFETY JOGGER

PROFESSIONAL

Heavy

BESTLIGHT1 OB

Medical Clogs Non-Slip

Designed for hygiene and comfort, Safety Jogger BESTLIGHT1 clogs are lightweight, washable, and slip-resistant. Perfect for medical and food industries.

| | |
|---------------|---|
| Upper | Expanded EVA |
| Lining | N/A |
| Footbed | SJ Basic 2 |
| Outsole | EVA/Rubber (NBR) |
| Category | OB / SRC |
| Size range | EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 JPN 21.5-31 / KOR 230-310 |
| Sample weight | 0.197 kg |
| Norms | ASTM F3445:2024 EN ISO 20347:2012 |



BLK




WHT



Washable 30°C

These shoes can be washed in a washing machine at 30°C.



Chemically & UV sterilizeable

This shoe is chemically and UV sterilizeable.

Industries:

Catering, Chemical, Cleaning, Food & beverages, Medical

Environments:

Dry environment, Extreme slippery surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20347 |
|----------------|---|-----------------------|-------------|--------------|
| Upper | Expanded EVA | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | N/A | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | N/A | ≥ 15 |
| Lining | N/A | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | N/A | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm ² | N/A | ≥ 20 |
| Footbed | SJ Basic 2 | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| Outsole | EVA/Rubber (NBR) | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 83.0 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.45 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.46 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.22 | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.32 | ≥ 0.18 |
| | Antistatic value | MegaOhm | N/A | 0.1 - 1000 |
| | ESD value | MegaOhm | N/A | 0.1 - 100 |
| | Heel energy absorption | J | N/A | ≥ 20 |

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.