

Ref. **9FRL010**

Multipurpose

Low

Low shoes



The +

- * Footbridge supplying torsional rigidity.
- * Padding for snug fit.
- * Metal free

PURCHASE PACKAGING

Ref.	Size	Carton
9FRL010036	36	6
9FRL010037	37	6
9FRL010038	38	6
9FRL010039	39	6
9FRL010040	40	6
9FRL010041	41	6
9FRL010042	42	6
9FRL010043	43	6
9FRL010044	44	6
9FRL010045	45	6
9FRL010046	46	6
9FRL010047	47	6
9FRL010048	48	6

Some sizes may only be available in certain countries



DESCRIPTION

Upper in granulated leather, water repellent
 External sole in PU double density
 Antipenetration textile sole, non-magnetic
 Composite toecap, non-magnetic
 Breathable textile lining

SECTORS

- Light Industries
- Manufacture of electrical and electronic equipment and machines
- Maintenance
- Infrastructure, building industry
- Construction - finishing work
- Transport (excluding manufacturing) and logistics
- Services and distribution

APPLICATIONS

Baggage handler
 Temporary work
 Delivery driver
 Maintenance
 Light industry

TECHNICAL FEATURES

Color	Black	Main assembly	Injected
Weight	596 g	Closing	Lacing closure
Upper	Full grain leather	Lining	Breathable 3D mesh
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		
Insole	Removable, textile and foam		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/02/25/0362 EXT 01/02/25

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2022

EN ISO 20345:2022
S3S

Safety shoes

S3S Basic requirements: a protective toe cap resistant to an impact of 200 Joule and a crushing of 15,000 Newton+ closed heel area- antistatic properties- energy-absorbing capacity of the heel Puncture resistance:- Resistance of the sole to puncture (min.1100 N and individual value $\geq$ 950 N) - Non-metallic insert, 3.0mm diameter puncture needle+ non-metallic insert type PS - resistance to penetration and water absorption of the upper- puncture resistance according to type- cleated outsole

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance

MAJ 12/05/2026